

	Type	L #	Hits	Search Text
1	BRS	L1	5641	( measur\$6 detect\$6 sens\$6 transducer ) near3 ( fuel ) near3 ( injection )
2	BRS	L2	1991	1 and ( measur\$6 detect\$6 sens\$6 transducer ) near3 ( temperature )
3	BRS	L3	1144	2 and ( measur\$6 detect\$6 sens\$6 transducer ) near3 ( pressure )
4	BRS	L4	759	3 and ( chamber )
5	BRS	L5	634	4 and ( ECU CPU controller microprocessor processor computer )
6	BRS	L6	45	5 and ( drain\$5 )
7	BRS	L7	43	6 and ( valve )
8	BRS	L8	25	7 and ( piston )
9	BRS	L9	9	8 and ( displacement )

	<b>DBs</b>	<b>Time Stamp</b>	<b>Comments</b>	<b>Error Definition</b>	<b>Errors</b>
1	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:23			0
2	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:23			0
3	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:24			0
4	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:24			0
5	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:25			0
6	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:25			0
7	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:26			0
8	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:26			0
9	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:26			0